

## WB3 Series Analytical Electronic Balance



WB3 Series Analytical Electronic Balance

### DETAILS:



**1**

**Dedicated power cord**  
CE certification is safer

**2**

**Level adjustment bubble**  
Adjust balance



**3**

**Anti-slip foot pad**  
Non-slip

### PRODUCT ACCESSORIES

#### Balance accessories details



power cord

F1 class stainless steel weight

a glove

stainless steel weighing pan

## WB3 Series Analytical Electronic Balance

### Product features:

1. Electromagnetic sensor
2. Aluminum shell/Large space wind proof cover
3. LCD (White back light with black font)
4. Tare function/Counting/Unit conversion  
(g/mg/ct/oz)...
5. Sensitivity/Speed set/Percentage
6. Overload alarm/Faultalarm/Level indicator
7. Option: Under weighing/Printer



**WB3 Series Product Specifications**

| WB3 Series Product Specifications |                                          |         |         |         |         |         |         |
|-----------------------------------|------------------------------------------|---------|---------|---------|---------|---------|---------|
| Model                             | WB3-100                                  | WB3-110 | WB3-120 | WB3-200 | WB3-210 | WB3-220 | WB3-300 |
| Capacity                          | 100g                                     | 110g    | 120g    | 200g    | 210g    | 220g    | 300g    |
| Resolution                        | 0.0001g                                  |         |         |         |         |         |         |
| Min weighing                      | 0.0004g                                  |         |         |         |         |         |         |
| Repeat ability                    | ±0.0002g                                 |         |         |         |         |         |         |
| Liner                             | ±0.0003g                                 |         |         |         |         |         |         |
| Stable Time                       | ≤3s                                      |         |         |         |         |         |         |
| Pan size                          | Φ80mm                                    |         |         |         |         |         |         |
| Display                           | LCD（white back light with black font）    |         |         |         |         |         |         |
| temperature                       | 15-35℃                                   |         |         |         |         |         |         |
| Draft shield size                 | 240x190x265mm                            |         |         |         |         |         |         |
| Appearance Size                   | 340x215x350mm                            |         |         |         |         |         |         |
| Option                            | Printer/Under weighing                   |         |         |         |         |         |         |
| Calibration                       | ExternalCalibration                      |         |         |         |         |         |         |
| Cal.weight                        | 100g                                     |         |         | 200g    |         |         |         |
| Communication                     | RS232C（Standard） 、 USB/Printer(Optional) |         |         |         |         |         |         |
| Packing Size                      | In:415x285x430mm    Ex:475x315x485mm     |         |         |         |         |         |         |
| G. weight                         | 10kg                                     |         |         |         |         |         |         |