

MB3 110 Moisture Analyzer

MB3 110 moisture analyzer configures high precision weighing sensor and high efficiency halogen



lamp heat device on the basis of electronic balance, to reach the rapid and accurate moisture determination. High quality and inexpensive.

This series is widely used in the scope of tobacco, paper making, food, tea, beverage, grain, chemical raw materials, pharmaceutical raw materials, texture raw materials etc., testing the moisture content of samples.

Features

Four Languages: Chinese, English, Germany, Spanish
Drying mode: Rapid, Standard, Gentle three modes
High accuracy Germany load cell
Display Moisture curve
By RS232 interface to connect printer and PC

Features

Sample weight just up 1g
Have Internal Temp. calibration
5inch Touch Screen, easy to operate
Can be saved 15 groups
Moisture Range from 0.01%

Model	MB3 110
Capacity	110g
Readability	0.001 g
Operating Temp	5°C-35°C
Display	LCD HD Back Display
Calibration	External Calibration
Interface	RS232/ (Estándar) USB (Opcional)
Pan Size	Ø90mm
Packing Size	490x350x360mm
Gross Weight	7.5kg
Heating Source	Halogen Lamp-2
Temp.Sensor	PT100
Temp.Range	40°C-199°C
Temp.Step	1°C
Moisture Range	0.00%-100.00%
Moisture Readability	0.01%
Dry Range	100.00%-0.00%
Dry Readability	0.01%
Temp Setting	40°C-199°C By 1°C Step
Time Setting	1-99min By 10s
Number Of Storage	15
Heater	220V ±15% 50HZ/110V±15% 60HZ/400W
Balance	Input:220V 50HZ/110V 60HZ Output:9V